

PINZAS PELACABLES Y PONCHADORAS

PINZAS PELACABLES CON MANGO AIR CUSHION



299



298




291P




293



292



297



291



296



- Mejor capacidad de corte y dureza en cuchillas.
- Exceden la norma ASME B107.500.

CÓDIGO	LONGITUD TOTAL	CALIBRE DE CABLE (AWG)		CORTA TORNILLOS						PONCHA TERMINALES	☐
		SÓLIDO	TRENZADO	10-24	6-32	8-32	10-32	4-40	5-40		
299	8-3/4"	8, 10, 12, 14, 16, 18	10, 12, 14, 16, 18, 20, 22	10-24	6-32	8-32	10-32	4-40	-	✓	3
298	8-1/4"	10, 12, 14, 16, 18, 20, 22	-	10-24	6-32	8-32	10-32	4-40	5-40	✓	3
291P	7-1/4"	10, 12, 14, 16, 18	12, 14, 16, 18, 20	-	6-32	8-32	-	-	-	✗	3
293	6"	22, 24, 26, 28, 30	-	-	-	-	-	-	-	✗	3
292	6-3/4"	16, 18, 20, 22, 24, 26	-	-	-	-	-	-	-	✗	3
297	6-3/4"	10, 12, 14, 16, 18, 20	-	-	-	-	-	-	-	✗	3
291	6-3/4"	10, 12, 14, 16, 18, 20	-	-	-	-	-	-	-	✗	3
296	4-29/32"	10-20	-	-	-	-	-	-	-	✗	3



PINZAS PELACABLE




PLC6



PLC8



PLC9



PLC10

- Cumplen la norma ASME B107.500.

CÓDIGO	LONGITUD TOTAL	CALIBRE DE CABLE	☐
PLC10	10"	10 - 22 AWG	1
PLC9	9"	10 - 24 AWG	1
PLC8	8"	10 - 22 AWG	1
PLC6	6"	10 - 26 AWG	1

